



technical spec sheet

ZoneBarrier ZB24573

Protects thermal sensor electronics from transients caused by direct or indirect lightning strikes.

- Hybrid fast acting Silicon Avalanche Diodes (SADs) with no resistors
- Mounting on standard 35mm DIN rail or to any flat surface for standalone applications
- 10 year product warranty



Specifications

Circuit Type:	Series hybrid
Lines protected:	Four (4)
Connectors:	5 positions cage clamp terminal strip
Surge capacity:	2,000A 8/20 impulse per line
Clamp voltage:	Signal - 10V @ 2kA 8/20
Rated voltage:	Signal - 7.5V
Max. leakage current:	5 μ A @ rated voltage
Max. inline resistance:	None
Case dimensions:	5.1" x 2.3" x 1.0" overall (12.95mm x 5.8mm x 2.54mm)

www.mtl-inst.com

enquiry@mtl-inst.com

**COOPER** Crouse-Hinds

EUROPE (EMEA): +44 (0)1582 723633
enquiry@mtl-inst.com

THE AMERICAS: +1 800 835 7075
csinfo@mtl-inst.com

ASIA-PACIFIC: +65 6 487 7887
sales@mtlsing.com.sg

ZB24573 Rev B 160310

The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes.