

Zone Surge Protection Devices

Proven to cut downtime and replacement part costs

| | |
|------------------------|---|
| PRODUCT SERIES: | ZONEBARRIER: “The effective barrier between surges and sensitive I/O ports.” |
| ORDER #: | ZB24579 |
| APPLICATION: | Protects 24Vac or 24Vdc lines from transients caused by direct or indirect lightning. |
| TECHNOLOGY: | The suppressor is a hybrid type employing high energy metal oxide varistors (MOV). The MOVs are monitored with a thermal sensitive device that disconnects the MOV if a failure occurs. The suppressor will indicate a failure when the green LED goes out. |
| INSTALLATION: | This ZoneBarrier can be mounted on a standard 35mm DIN rail, or to any flat surface for standalone applications. |

SPECIFICATIONS:

Circuit Type: Hybrid
Lines Protected: 3 (L, N, G)
Cage Clamp: Terminal Strip
Surge Capacity: 13kA 8/20 impulse
Clamp Voltage: 90V @ 2kA 8/20
MCOV: 30Vac, 38Vdc
Max Load Current: 16 Amperes
Case Dimensions: 5.1” x 2.3” x 1.0” overall



For more information please contact your local sales office:

| | | | |
|----------------------|--------------------|-------------------------|--------------------|
| The Americas: | +1 800 835 7075 | The Netherlands: | +31 (0)481 450250 |
| UK: | +44 (0)1582 723633 | Italy: | +39 (0)2 6180 2011 |
| Singapore: | +65 6 487 7887 | Australia: | +61 (0)8 9455 2994 |
| | | India: | +91 (0)44 450 1660 |

Local sales office information is also available on our web site at: www.mtl-inst.com/contact/

